

E800



HIGH-PERFORMANCE GNSS RECEIVER

■ 5-Watt Internal Radio: Longer Working Distance

No longer need to carry external radio, for its internal radio's working distance can reach 10 - 15 km.

■ Impressive Battery Life: Longer Working Time

Work up to 15 hours and no longer worry about a day's work, with its 13600 mAh battery, which makes your data save safely.

■ 1.45-inch Display: Colorful and Touchable

View the primary status and basic information, set the work mode, and operate the device, facilitating more convenient and direct human-computer interaction.

■ RTK Assistant Technology: Uninterrupted Work

Work without interruption even when RTK corrections fail, powered by our RTK assistant technology.

■ Max 60° Tilt Survey: A Different Way of Working

- Quickly measure accurate points while standing or walking without leveling the pole.
- Concentrate on where the pole tip needs to go, which is especially useful during a stakeout.
- Easily start a survey in environments that are hard to reach, such as building corners and slopes.
- No longer worry about the movement of the pole when measuring, provided that the pole tip is stationary.

The eSurvey 800 is a high-performance product by eSurvey GNSS. The durable IP67 design makes it possible to work in various of environments. Multi constellation and frequency tracking always gives a Fixed solution for your job. The colorful touch screen is convenient for quick configurations.

Specification

GNSS Performance		
Satellites tracking	GPS	L1CA, L2P(Y), L2C, L5
	BDS	B1I, B2I, B3I, B1C, B2a, B2b ¹
	GLONASS	L1, L2
	GALILEO	E1, E5a, E5b, E6 ¹
	QZSS	L1, L2, L5, L6 ¹
	L-Band	B2b PPP (Only for the Asian-Pacific region)
Channels	1408	
Cold start	< 30 seconds	
Warm start	< 20 seconds	
Hot start	< 5 seconds	
RTK signal initialization	< 5 seconds	
Initialization reliability	> 99.9%	
Update rate	20 Hz	
High precision static	<ul style="list-style-type: none"> ■ H: 3 mm + 1 ppm RMS ■ V: 5 mm + 1 ppm RMS 	
RTK	<ul style="list-style-type: none"> ■ H: 8 mm + 1 ppm RMS ■ V: 15 mm + 1 ppm RMS 	
Standard point positioning	<ul style="list-style-type: none"> ■ H: 1.5 m RMS ■ V: 2.5 m RMS 	
Code differential	<ul style="list-style-type: none"> ■ H: 0.4 m RMS ■ V: 0.8 m RMS 	
Correction data	RTCM V3.X, RTCM2, CMR	
Data output	GGA, ZDA, GSA, GSV, GST, VTG, RMC, GLL, Binary	

Power Supply	
Battery	Rechargeable Built-in Lithium-ion battery x 1 7.2V ~ 13600 mAh
Voltage	9 - 28V dc
Working time	15 hours
Charging time	Typically 5 hours

Internet Modem	
Supported band	Global 4G <ul style="list-style-type: none"> ■ LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B18, B19, B20, B25, B26, B28 ■ LTE TDD: B38, B39, B40, B41 ■ UMTS: B1, B2, B4, B5, B6, B8, B19 ■ GSM: B2, B3, B5, B8

1: It is not supported for now. It will be supported after firmware update in the future.

2: It varies with the obstacle and terrain.

3: It is only available for radio protocol "Satel", and the radio firmware is later than G001.02.27.

System	
Operation system	Linux
Internal memory	32 GB
Bluetooth	BT5.0+EDR, BLE
Wi-Fi	802.11 a/b/g/n/ac
SIM card	√
TNC	Connect internal radio with antenna
5-pin port	Connect to external radio and external power
Type-C port	Charge and data transmission
Web UI	View status, update firmware, set up working mode, download data, etc.
Intelligent voice	Broadcast working mode and status
MEMS	Fast initialization, dynamic tilt survey up to 60°

Physical	
Dimension	Φ154 mm x H76 mm
Weight	1500 g
Operating temperature	-30°C - +65°C
Storage temperature	-40°C - +80°C
Water / dust proof	IP67
Shock	<ul style="list-style-type: none"> ■ Withstand topple over from a 2 m survey pole onto hard surfaces ■ Survive a 1.2 m free drop
Vibration	Vibration resistant
Humidity	Up to 100%
Indicators	Satellites, datalink, battery, Bluetooth
Button	Power button, short press to voice broadcast working mode and status
Screen	1.45" colorful touchable screen
Certificate	CE, FCC, NGS

Internal Radio	
Type	TX and RX
Emitting Power	5 W
Operation Range	<ul style="list-style-type: none"> ■ 8 - 10 km typically ■ 15 km with optimal conditions²
Frequency range	410 - 470 MHz
Channel spacing	6.25 KHz ³ / 12.5 KHz / 25 KHz
Protocol	Satel, PCC, TrimTalk, TrimMark III, TRANSEOT(PCC-GMSK), South, HiTarget, GEOTALK, GEOMK3, HZSZ

